



GRANDSTREAM
CONNECTING THE WORLD



A simple and reliable IP Phone

GXP1610/1615

A simple IP phone for small business users, the GXP1610/1615 delivers a user-friendly VoIP calling experience in a very easy-to-use IP phone. The GXP1610/1615 offers support for 1 line, 2 call appearances and includes 3-way voice conferencing to maximize productivity. Additional features include a 132x48 (2.95") LCD screen for easy viewing, 3 XML programmable soft keys for customization, 10/100 mbps ports, integrated PoE on the GXP1615 model, EHS support for Plantronics headsets and multi-language support. These features allow the GXP1610/GXP1615 to be a high-quality small business IP phone that is simple and easy-to-use.



1 SIP account,
up to 2 call
appearances



TLS and SRTP
security encryption
technology to
protect calls and
accounts



3-way audio
conferencing for easy
conference calls



Electronic Hook Switch
(EHS) support for
Plantronics headsets



Automated
provisioning
options include
TR-069 and XML
config files



Full-duplex
speakerphone
with HD audio
to maximize
audio quality
and clarity



Use with
Grandstream's UCM
series of IP PBXs
for Zero Config
provisioning



Built-in PoE 802.3af
to power the
device and give it a
network connection
(GXP1615 only)

| | |
|--|---|
| Protocols/Standards | SIP RFC3261, TCP/IP/UDP, RTP/RTCP, HTTP/HTTPS, ARP/RARP, ICMP, DNS (A record, SRV, NAPTR), DHCP, PPPoE, SSH, TFTP, NTP, STUN, SIMPLE, LLDP-MED, LDAP, TR-069, 802.1x, TLS, SRTP, CDP/SNMP/RTCP-XR |
| Network Interfaces | Dual switched auto-sensing 10/100 Mbps Ethernet ports, integrated PoE (GXP1615 only) |
| Graphic Display | 132 x 48 (2.95") LCD display |
| Feature Keys | 2 line keys with dual-color LED and 1 SIP account, 3 XML programmable context sensitive soft keys, 5 (navigation, menu) keys. 13 dedicated function keys for PAGE/INTERCOM, PHONEBOOK, MESSAGE, HOME, HOLD, RECORD, MUTE, HEADSET, TRANSFER, CONFERENCE, SEND and REDIAL, SPEAKERPHONE, VOLUME |
| Voice Codecs | Support for G.711μ/a, G.722 (wide-band), G.723, G.726-32, G.729 A/B, iLBC, in-band and out-of-band DTMF (In audio, RFC2833, SIP INFO), VAD, CNG, AEC, PLC, AJB, AGC |
| Telephony Features | Hold, transfer, forward (unconditional/no-answer/busy), 3-way conferencing, call park/pickup, downloadable phone book (XML, LDAP, up to 1000 items), call waiting, call history (up to 200 records), off-hook auto dial, auto answer, click-to-dial, flexible dial plan, hot desking, personalized music ringtones, server redundancy & fail-over |
| Headset Jack | RJ9 headset jack (allowing EHS with Plantronics headsets) |
| Base Stand | Yes, 2 angled positions available, wall mountable |
| Wall Mountable | Yes |
| QoS | Layer 2 QoS (802.1Q, 802.1P) and Layer 3 (ToS, DiffServ, MPLS) QoS |
| Security | User and administrator level access control, MD5 and MD5-sess based authentication, 256-bit AES encrypted configuration file, TLS, SRTP, HTTPS, 802.1x media access control |
| Multi-language | English, German, Italian, French, Spanish, Portuguese, Russian, Croatian, simplified and traditional Chinese, Korean, Japanese and more |
| Upgrade/Provisioning | Firmware upgrade via TFTP / HTTP / HTTPS, mass provisioning using TR-069 or AES encrypted XML configuration file, FTP/FTPS |
| Power & Green Energy Efficiency | Universal Power Supply Input 100-240VAC 50-60Hz; Output +5VDC, 600mA; PoE: IEEE802.3af Class 2, 3.84W-6.49W; IEEE802.3az (EEE) (GXP1615 Only) |
| Physical | Dimension: 209mm (L) x 184.5mm (W) x 76.2mm (H) (with handset) Unit weight: 0.74kg; Package weight: 1.1kg |
| Temperature and Humidity | Operation: 0°C to 40°C, Storage: -10°C to 60°C, Humidity: 10% to 90% Non-condensing |
| Package Content | GXP1610/1615 phone, handset with cord, base stand, universal power supply, network cable, Quick Installation Guide, brochure, GPL License |
| Compliance | FCC: Part 15 (CFR 47) Class BCE : EN55022 Class B, EN55024, EN61000-3-2, EN61000-3-3, EN60950-1RCM: AS/ACIF S004; AS/NZS CISPR22/24; AS/NZS 60950; AS/NZS 60950.1 |